


| REV | DATE     | COMMENTS   | INITIALS |
|-----|----------|------------|----------|
| H   | 26APR22  | ECO-001915 | GW       |
| G   | 19MAY20  | ECO-001066 | AKC      |
| F   | 07APR20  | ECO-001046 | AKC      |
| E   | 04Sept18 | DCR3079    | JHM      |
| D   | 16MAY18  | DCR2702    | LY       |

ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE STATED.  
 DIMENSIONS, TOLERANCES, SYMBOLS AND SURFACE TEXTURES ARE IN ACCORDANCE WITH BS 8888, UNLESS OTHERWISE STATED.  
 WELD SYMBOLS ARE IN ACCORDANCE WITH BS EN ISO 2553.  
 REMOVE ALL BURRS AND SHARP EDGES.

DO NOT SCALE  
 IF IN DOUBT, ASK



**slingco**

SLINGCO LIMITED  
 STATION ROAD, FACIT,  
 WHITWORTH, LANCASHIRE, OL12 8LJ  
 e-mail: sales@slingco.com  
 http://www.slingco.com

SLINGCO AMERICA, INC  
 130 CELTIC BLVD,  
 TYRONE, GEORGIA, 30290  
 e-mail: sales@slingco.com  
 http://www.slingco.com

ALL DIMENSIONS MEASURED ON A  
 MEAN DIAMETER

DIMENSIONAL TOLERANCE  $\pm 5\%$

STATE  
 Released A3

DRAWN CM  
 14 October/2009 00:00:00

CHECKED DD

SCALE  
 NTS

BREAK LOAD  
 7212KGS / 15900LBS

GRIP TYPE  
 NS TYPE

MINIMUM DIAMETER  
 65MM (2.5")

MAXIMUM DIAMETER  
 80MM (3.0")

PROJECT No

PROJECT

CUSTOMER

CUSTOMER DRAWING No

TITLE  
 NON-CONDUCTIVE (ARAMID)  
 SINGLE EYE DOUBLE WEAVE  
 CABLE GRIP - DATA SHEET

PART No  
 ZCS1180

REV  
 H

SHEET  
 1 OF 1